Supplier's name or trade mark: ARÇELİK					
Supplier's address: Arçelik Pazarlama A.Ş. Caferağa Mah. Albay Faik Sözdener Cd. No:19 Kadıköy / İstanbul					
Model identifier: 1280 YKMP IG 457000010100					
General product parameters:					
Parameter	Value		Parameter	Value	
Rated capacity (kg)	Rated capacity	8,0	Dimensions in cm	Height	84,5
	Rated washing capacity	12,0		Width Depth	60 60
Energy Efficiency Index	EEI _W	46,5	Energy efficiency class	EEI _W	A
	EEI _{WD}	66,9		EEI _{WD}	D
Washing efficiency index	I_{W}	1,031	Rinsing effectiveness (g/kg dry textile)	I_R	4,9
	$ m J_W$	1,031		J_R	4,9
Energy consumption in kWh per cycle, for the washing cycle of the household washer-dryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used	0,463		Energy consumption in kWh per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used	3,704	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	55		Water consumption in litre per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	78	
Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer-dryer, using the eco 40-60 programme	Rated washing capacity	34	Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer-dryer,	Rated capacity	29
	Half	30	using the wash and dry cycle	Half	25
Spin speed (rpm)	Quarter	23			
	Rated washing capacity	1351	Waishad associates associates associate (00)	53,9	
	Half	1351	Weighted remaining moisture content (%)		
	Quarter Rated washing	1351			
Eco 40-60 programme duration (h:min)	capacity	3:59	Spin-drying efficiency class	B Rated 0.25	
	Half	2:59			
	Quarter	2:59			
Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	77		wash and dry cycle duration (h:min)	capacity Half	9:25 6:40
Туре	Free-Standing		Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	С	
Off-mode (W) (if applicable)	0,50		Standby mode (W) (if applicable)	0,50	
Delay start (W) (if applicable)	4,00		Networked standby (W) (if applicable)	2,00	
Minimum duration of the guarantee offered by the supplier: 24 months					
This product has been designed to release silver ions during the washing cycle NO					
Additional information:					
Weblink to the supplier's website, where the information in point 9 of Annex II to Regulation (EU) 2019/2023 is found: https://www.arcelik.com.tr/destek					