

Supplier's name or trade mark:			ARÇELİK		
Supplier's address:			Arçelik A.Ş. Karaağaç Caddesi No:2-6,34445, Sütlüce Beyoğlu/İstanbul		
Model identifier:			8051 YK 7161510100		
General product parameters:					
Parameter	Value		Parameter	Value	
Rated capacity (kg)	Rated capacity	5,0	Dimensions in cm	Height	84,0
	Rated washing capacity	8,0		Width	60,0
				Depth	59,0
Energy Efficiency Index	EEI _W	68,5	Energy efficiency class	EEI _W	C
	EEI _{WD}	66,5		EEI _{WD}	D
Washing efficiency index	I _W	1,040	Rinsing effectiveness (g/kg dry textile)	I _R	4,9
	J _W	1,040		J _R	4,9
Energy consumption in kWh per cycle, for the washing cycle of the household washer-dryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used	0,623		Energy consumption in kWh per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used	2,641	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	40		Water consumption in litre per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	53	
Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer- dryer, using the eco 40-60 programme	Rated washing capacity	40	Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer-dryer, using the wash and dry cycle	Rated capacity	25
	Half	32		Half	24
	Quarter	23			
Spin speed (rpm)	Rated washing capacity	1400	Weighted remaining moisture content (%)	53,0	
	Half	1400			
	Quarter	1400			
Eco 40-60 programme duration (h:min)	Rated washing capacity	3:38	Spin-drying efficiency class	B	
	Half	2:47			
	Quarter	2:47			
Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	76		wash and dry cycle duration (h:min)	Rated capacity	7:55
				Half	5:50
Type	Free-Standing		Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	B	
Off-mode (W) (if applicable)	0,50		Standby mode (W) (if applicable)	0,50	
Delay start (W) (if applicable)	4,00		Networked standby (W) (if applicable)	2,00	
Minimum duration of the guarantee offered by the supplier : 24 months					
This product has been designed to release silver ions during the washing cycle				NO	
Additional information:					
Weblink to the supplier's website, where the information in point 9 of Annex II to Regulation (EU) 2019/2023 is found : https://www.arcelik.com.tr/destek					