

Supplier’s name or trade mark:			Beko		
Supplier’s address:			Arçelik Pazarlama A.Ş. Caferağa Mah. Albay Faik Sözdener Cd. No:19 Kadıköy / İstanbul		
Model identifier:			BK 851 YKI 7164041800		
General product parameters:					
Parameter	Value		Parameter	Value	
Rated capacity (kg)	Rated capacity	5,0	Dimensions in cm	Height	84
	Rated washing capacity	8,0		Width	60
				Depth	59
Energy Efficiency Index	EEI _W	68,5	Energy efficiency class	EEI _W	C
	EEI _{WD}	66,5		EEI _{WD}	D
Washing efficiency index	I _W	1,04	Rinsing effectiveness (g/kg dry textile)	I _R	4,9
	J _W	1,04		J _R	4,9
Energy consumption in kWh per kg per cycle, for the washing cycle of the household washer-dryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used	0,078		Energy consumption in kWh per kg per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used	0,528	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	40,0		Water consumption in litre per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	53	
Maximum temperature inside the treated textile (°C)	Rated washing capacity	40	Remaining moisture content (%)	Rated washing capacity	53
	Half	32		Half	53
	Quarter	23		Quarter	53
Spin speed (rpm)	Rated washing capacity	1400	Spin-drying efficiency class	B	
	Half	1400			
	Quarter	1400			
Eco 40-60 programme duration (h:min)	Rated washing capacity	3:38	wash and dry cycle duration (h:min)	Rated capacity	7:55
	Half	2:47		Half	5:50
	Quarter	2:47			
Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	76		Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	B	
Type	Free-Standing				
Off-mode (W)	0,50		Standby mode (W)	0,50	
Delay start (W) (if applicable)	4,00		Networked standby (W) (if applicable)	2,00	
Minimum duration of the guarantee offered by the supplier : 24 months					
This product has been designed to release silver ions during the washing cycle				NO	
Additional information:					
Weblink to the supplier’s website, where the information in point 9 of Annex II to Regulation (EU) 2019/2023 is found : N/A					