Supplier's name or trade mark:

ARÇELİK

Supplier's address :

Arçelik A.Ş. Karaağaç Caddesi No:2-6,34445, Sütlüce Beyoğlu/İstanbul

Model identifier:

11140 M 7164171200

| General | product | parameters: |
|---------|---------|-------------|
|---------|---------|-------------|

Delay start (W) (if applicable)

during the washing cycle

Minimum duration of the guarantee offered by the supplier :

This product has been designed to release silver ions

| Parameter | Value | | Parameter | Value | |
|---|----------------|------|---|---------------|------|
| | 11,0 | | | Height | 84,0 |
| Rated capacity (kg) | | | Dimensions in cm | Width | 60,0 |
| | | | | Depth | 67,0 |
| Energy efficiency index (EEI_w) | 51,5 | | Energy efficiency class | А | |
| Washing efficiency index | 1,035 | | Rinsing effectiveness (g/kg) | 4,9 | |
| Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. | 0,525 | | Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water. | 48 | |
| Maximum temperature inside the treated textile (°C) | Rated capacity | 34 | | 53,9 | |
| | Half | 30 | Weighted remaining moisture content (%) | | |
| | Quarter | 22 | 1 | | |
| Spin speed (rpm) | Rated capacity | 1400 | | В | |
| | Half | 1400 | Spin-drying efficiency class | | |
| | Quarter | 1400 | | | |
| Programme duration (h:min) | Rated capacity | 3:59 | | Free-Standing | |
| | Half | 2:59 | Туре | | |
| | Quarter | 2:59 | | | |
| Airborne acoustical noise emissions in the spinning phase (dB(A) re 1 pW) | 74 | | Airborne acoustical noise emission class (spinning phase) | В | |
| Off-mode (W) (if applicable) | 0,50 | | Standby mode (W) (if applicable) | 1,00 | |

Networked standby (W) (if applicable)

24 months

NO

4,00

NA