| Supplier's name or trade mark:  ARÇELİK   |                |      |  |               |      |
|---|----------------|------|--|---------------|------|
| Supplier's address : Arçelik A.Ş. Karaağaç Caddesi No:2-6,34445, Sütlüce Beyoğlu/İstanbul   |                |      |  |               |      |
| Model identifier: 11141 M 7164171300  |                |      |  |               |      |
| General product parameters:   |                |      |  |               |      |
| Parameter   | Value          |      | Parameter  | Value         |      |
| Rated capacity (kg)   | 11,0           |      | Dimensions in cm   | Height        | 84,0 |
|   |                |      |  | Width         | 60,0 |
|   |                |      |  | Depth         | 67,0 |
| Energy efficiency index (EEI <sub>w</sub> )   | 51,5           |      | Energy efficiency class  | А             |      |
| Washing efficiency index  | 1,035          |      | Rinsing effectiveness (g/kg)   | 4,9           |      |
| Energy consumption in kWh per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used. | 0,525          |      | Water consumption in litre per cycle, based on the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water. | 48            |      |
| Maximum temperature inside the treated textile (°C)   | Rated capacity | 34   |  | 53,9          |      |
|   | Half           | 30   | Weighted remaining moisture content (%)  |               |      |
|   | Quarter        | 22   | , ,  |               |      |
| Spin speed (rpm)  | Rated capacity | 1400 |  |               |      |
|   | Half 1400      |      | Spin-drying efficiency class   | В             |      |
|   | Quarter        | 1400 |  |               |      |
| Programme duration (h:min)  | Rated capacity | 3:59 |  |               |      |
|   | Half 2:59      |      | Туре   | Free-Standing |      |
|   | Quarter        | 2:59 |  |               |      |
| Airborne acoustical noise emissions in the spinning phase (dB(A) re 1 pW)   | 74             |      | Airborne acoustical noise emission class (spinning phase)  | В             |      |
| Off-mode (W) (if applicable)  | 0,50           |      | Standby mode (W) (if applicable)   | 1,00          |      |
| Delay start (W) (if applicable)   | 4,00           |      | Networked standby (W) (if applicable)  | NA            |      |
| Minimum duration of the guarantee offered by the supplier :   |                |      | 24 months  |               |      |
| This product has been designed to release silver ions during the washing cycle  |                |      | NO   |               |      |
| Additional information:   |                |      |  |               |      |
| Weblink to the supplier's website, where the information in point 9 of Annex II to Commission Regulation (EU) 2019/2023 is found: https://www.arcelik.com.tr/destek                   |                |      |  |               |      |