Supplier's name or trade mark: ARÇELİK					
Supplier's address: Arçelik A.Ş. Karaağaç Caddesi No:2-6,34445, Sütlüce Beyoğlu/İstanbul					
Model identifier: 1280 YKM 7175722600					
General product parameters:					
Parameter	Value		Parameter	Value	
Rated capacity (kg)	Rated capacity	8,0		Height	84,5
	Rated washing capacity	12,0	Dimensions in cm	Width	60,0
				Depth	65,0
Energy Efficiency Index	$EEI_{\mathbf{W}}$	51,5	Energy efficiency class	$EEI_\mathbf{W}$	Α
	EEI _{WD}	66,9		EEI _{WD}	D
Washing efficiency index	$I_{\mathbf{W}}$	1,031	Rinsing effectiveness (g/kg dry textile)	I_R	4,9
	$ m J_W$	1,031		J_{R}	4,9
Energy consumption in kWh per cycle, for the washing cycle of the household washer-dryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used	0,463		Energy consumption in kWh per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used	3,704	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	55		Water consumption in litre per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	78	
Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer- dryer, using the eco 40-60 programme Spin speed (rpm)	Rated washing capacity	34	Maximum temperature inside the treated textile (°C)	Rated capacity	29
	Half	30	for the washing cycle of the household washer-dryer, using the wash and dry cycle	Half	25
	Quarter	23		11411	
	Rated washing capacity	1400	W. 1. 1	0,0	
	Half	1400	Weighted remaining moisture content (%)		
	Quarter Rated washing	1400			
Eco 40-60 programme duration (h:min) Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	capacity 5.59		Spin-drying efficiency class	В	
	Half 2:59				
	Quarter	2:59		Rated	0.05
	77		wash and dry cycle duration (h:min)	capacity	9:25
				Half	6:40
Туре	Free-Standing		Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	С	
Off-mode (W) (if applicable)	0,50		Standby mode (W) (if applicable)	0,50	
Delay start (W) (if applicable)	4,00		Networked standby (W) (if applicable)	2,00	
Minimum duration of the guarantee offered by the supplier: 24 months					
This product has been designed to release silver ions during the washing cycle NO					
Additional information:					
Weblink to the supplier's website, where the information in point 9 of Annex II to Regulation (EU) 2019/2023 is found: https://www.arcelik.com.tr/destek					