Supplier's name or trade mark: ARÇELİK					
Supplier's address: Arçelik Pazarlama A.Ş. Caferağa Mah. Albay Faik Sözdener Cd. No:19 Kadıköy / İstanbul					
Model identifier: 8050 YKMI 7175750700					
General product parameters:					
Parameter	Value		Parameter	Value	
Rated capacity (kg)	Rated capacity	5,0	Dimensions in cm	Height	84,5
	Rated washing capacity	8,0		Width Depth	60,0 57,0
Energy Efficiency Index	$\mathrm{EEI}_{\mathbf{W}}$	51,5	Energy efficiency class	EEI _W	А
	EEI _{WD}	66,5		EEI _{WD}	D
Washing efficiency index	$I_{\mathbf{W}}$	1,035	Rinsing effectiveness (g/kg dry textile)	I_R	4,9
	J_{W}	1,035		J_R	4,9
Energy consumption in kWh per cycle, for the washing cycle of the household washer-dryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used	0,468		Energy consumption in kWh per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used	2,641	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	46		Water consumption in litre per cycle, for the wash and dry cycle of the household washer-dryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water	65	
Maximum temperature inside the treated textile (°C) for the washing cycle of the household washer- dryer, using the eco 40-60 programme Spin speed (rpm)	Rated washing capacity	29	Maximum temperature inside the treated textile (°C)	Rated capacity	28
	Half	27	for the washing cycle of the household washer-dryer, using the wash and dry cycle	Half	22
	Quarter Rated washing	22		11411	
	capacity	1400		53,9	
	Half	1400	Weighted remaining moisture content (%)		
	Quarter Rated washing	1400			
Eco 40-60 programme duration (h:min)	Half 2:47		Spin-drying efficiency class	В	
	Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	76		wash and dry cycle duration (h:min)	capacity Half
Туре	Free-Standing		Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	В	
Off-mode (W) (if applicable)	0,50		Standby mode (W) (if applicable)	0,50	
Delay start (W) (if applicable)	4,00		Networked standby (W) (if applicable)	2,00	
Minimum duration of the guarantee offered by the supplier: 24 months					
This product has been designed to release silver ions during the washing cycle NO					
Additional information:					
Weblink to the supplier's website, where the information in point 9 of Annex II to Regulation (EU) 2019/2023 is found: https://www.arcelik.com.tr/destek					