| PRODUCT FICHE                                       |                          |         |  |
|---|--------------------------|---------|--|
| Energy Label Directive EU2010/30/EU-                | No65/2014 of range hoods |         |  |
| Brand   | ARÇELİK                  |         |  |
| Model   | ADT 606-2 B              |         |  |
| Annual Energy Consumption( AEC hood)(kWh/a)         |                          | 58,3    |  |
| Energy Efficiency Class                             |                          | A       |  |
| Fluid Dynamic Efficiency (FDE hood)                 |                          | 29,1    |  |
| Fluid Dynamic Efficiency Class                      |                          | А       |  |
| Lighting Efficiency (LE hood) (lux/watt)            |                          | 34      |  |
| Lighting Efficiency Class                           |                          | А       |  |
| Grease Filtering Efficiency                         |                          | 86,0    |  |
| Grease Filtering Efficiency Class                   |                          | в       |  |
| Air flow (m³/h) (min. and max. setting)             |                          | 204-425 |  |
| Air flow (m³/h) (boost setting)                     |                          | 710     |  |
| Sound power level (dB) (min. and max. setting)      |                          | 43-60   |  |
| Sound power level (dB) (boost setting)              |                          | 71      |  |
| Measured power consumption in standby mode (Ps) (W) |                          | 0,25    |  |
| Measured power consumption off mode (Po)(W)         |                          | -       |  |
|   |                          |         |  |

7703330202 185373333 AA en\_US

| INSTRUCTION BOOKLET  |                         |      |
|--|-------------------------|------|
| Information for domestic range hoods   |                         |      |
| Comply with EU directive 2009/125/   | C Regulation No 66/2014 |      |
| Brand  | ARÇELİK                 |      |
| Model  | ADT 606-2 B             |      |
| Annual Energy Consumption( AEC hood)(kWh/a)  |                         | 58,3 |
| Time increase factor (f)   |                         | 0,9  |
| Fluid Dynamic Efficiency (FDE hood)  |                         | 29,1 |
| Energy Efficiency Index (EEI hood)   |                         | 54,6 |
| Measured air flow rate at best efficiency point (QBEP ) (m³/h)                     |                         | 378  |
| Measured air pressure at best efficiency point (PBEP) (Pa)                         |                         | 456  |
| Maximum air flow (Q max) (m³/h)  |                         | 710  |
| Measured electric power input at best efficiency point(WBEP) (W)                   |                         | 160  |
| Nominal power of the lighting system (WL)(W)                                       |                         | 5,5  |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) |                         | 189  |
| Measured power consumption in standby mode (Ps) (W)                                |                         | 0,25 |
| Measured power consumption off mode (Po)(W)  |                         | -    |
| Sound power level (LWA)(dB)  |                         | 60   |
|  | 220202 405272222 44     |      |

7703330202 185373333 AA en\_US