| PRODUCT FICHE | | | |
|--|------------|---------|--|
| Energy Label Directive EU2010/30/EU-No65/2014 of range hoods | | | |
| Brand | Beko | | |
| Model | BDE 6062 D | | |
| Annual Energy Consumption(AEC hood)(kWh/a) | | 58,5 | |
| Energy Efficiency Class | | А | |
| Fluid Dynamic Efficiency (FDE hood) | | 30 | |
| Fluid Dynamic Efficiency Class | | Α | |
| Lighting Efficiency (LE hood) (lux/watt) | | 32 | |
| Lighting Efficiency Class | | Α | |
| Grease Filtering Efficiency | | 76 | |
| Grease Filtering Efficiency Class | | С | |
| Air flow (m³/h) (min. and max. setting) | | 220-445 | |
| Air flow (m³/h) (boost setting) | | 720 | |
| Sound power level (dB) (min. and max. setting) | | 44-60 | |
| Sound power level (dB) (boost setting) | | 70 | |
| Measured power consumption in standby mode (Ps) (W) | | 0,25 | |
| Measured power consumption off mode (Po)(W) | | - | |
| | | | |

7704330105 185373496 AA en_US

| INSTRUCTION BOOKLET | | |
|--|-------------------------|-------|
| Information for domestic range hoods | | |
| Comply with EU directive 2009/125/E | C Regulation No 66/2014 | |
| Brand | Beko | |
| Model | BDE 6062 D | |
| Annual Energy Consumption(AEC hood)(kWh/a) | | 58,5 |
| Time increase factor (f) | | 0,9 |
| Fluid Dynamic Efficiency (FDE hood) | | 30 |
| Energy Efficiency Index (EEI hood) | | 54 |
| Measured air flow rate at best efficiency point (QBEP) (m³/h) | | 407,2 |
| Measured air pressure at best efficiency point (PBEP) (Pa) | | 433,5 |
| Maximum air flow (Q max) (m³/h) | | 720 |
| Measured electric power input at best efficiency point(WBEP) (W) | | 162,4 |
| Nominal power of the lighting system (WL)(W) | | 5.5 |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) | | 175 |
| Measured power consumption in standby mode (Ps) (W) | | 0,25 |
| Measured power consumption off mode (Po)(W) | | - |
| Sound power level (LWA)(dB) | | 60 |

7704330105 185373496 AA en_US