

PRODUCT FICHE

Energy Label Directive EU2010/30/EU-No65/2014 of range hoods

| | |
|--|-------------|
| Brand | ARÇELİK |
| Model | ADE 606-4 G |
| Annual Energy Consumption(AEC hood)(kWh/a) | 58,5 |
| Energy Efficiency Class | A |
| Fluid Dynamic Efficiency (FDE hood) | 30 |
| Fluid Dynamic Efficiency Class | A |
| Lighting Efficiency (LE hood) (lux/watt) | 32 |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency | 76 |
| Grease Filtering Efficiency Class | C |
| Air flow (m ³ /h) (min. and max. setting) | 220-445 |
| Air flow (m ³ /h) (boost setting) | 720 |
| Sound power level (dB) (min. and max. setting) | 44-60 |
| Sound power level (dB) (boost setting) | 70 |
| Measured power consumption in standby mode (Ps) (W) | 0,25 |
| Measured power consumption off mode (Po)(W) | - |

7704330116 185373953 AA en_US

INSTRUCTION BOOKLET**Information for domestic range hoods**

Comply with EU directive 2009/125/EC Regulation No 66/2014

| | | |
|--|-------------|-------|
| Brand | ARÇELİK | |
| Model | ADE 606-4 G | |
| Annual Energy Consumption(AEC hood)(kWh/a) | | 58,5 |
| Time increase factor (f) | | 0,9 |
| Fluid Dynamic Efficiency (FDE hood) | | 30 |
| Energy Efficiency Index (EEI hood) | | 54 |
| Measured air flow rate at best efficiency point (QBEP) (m ³ /h) | | 407,2 |
| Measured air pressure at best efficiency point (PBEP) (Pa) | | 433,5 |
| Maximum air flow (Q max) (m ³ /h) | | 720 |
| Measured electric power input at best efficiency point(WBEP) (W) | | 162,4 |
| Nominal power of the lighting system (WL)(W) | | 5.5 |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) | | 175 |
| Measured power consumption in standby mode (Ps) (W) | | 0,25 |
| Measured power consumption off mode (Po)(W) | | - |
| Sound power level (LWA)(dB) | | 60 |

7704330116 185373953 AA en_US