

PRODUCT FICHE

Energy Label Directive EU2010/30/EU-No65/2014 of range hoods

| | |
|---|-----------|
| Brand | ARÇELİK |
| Model | ADE 604 B |
| Annual Energy Consumption(AEC hood)(kWh/a) | 59 |
| Energy Efficiency Class | C |
| Fluid Dynamic Efficiency (FDE hood) | 20,3 |
| Fluid Dynamic Efficiency Class | C |
| Lighting Efficiency (LE hood) (lux/watt) | 32 |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency | 66,0 |
| Grease Filtering Efficiency Class | D |
| Air flow (m³/h) (min. and max. setting) | 226-408 |
| Air flow (m³/h) (boost setting) | - |
| Sound power level (dB) (min. and max. setting) | 43-56 |
| Sound power level (dB) (boost setting) | - |
| Measured power consumption in standby mode (Ps) (W) | 0,25 |
| Measured power consumption off mode (Po)(W) | - |

7704331110 185373382 AB en_US

INSTRUCTION BOOKLET**Information for domestic range hoods**

Comply with EU directive 2009/125/EC Regulation No 66/2014

| | |
|--|-----------|
| Brand | ARÇELİK |
| Model | ADE 604 B |
| Annual Energy Consumption(AEC hood)(kWh/a) | 59 |
| Time increase factor (f) | 1,3 |
| Fluid Dynamic Efficiency (FDE hood) | 20,3 |
| Energy Efficiency Index (EEI hood) | 70,6 |
| Measured air flow rate at best efficiency point (QBEP) (m ³ /h) | 271,1 |
| Measured air pressure at best efficiency point (PBEP) (Pa) | 319 |
| Maximum air flow (Q max) (m ³ /h) | 408 |
| Measured electric power input at best efficiency point(WBEP) (W) | 118 |
| Nominal power of the lighting system (WL)(W) | 5.5 |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) | 175 |
| Measured power consumption in standby mode (Ps) (W) | 0,25 |
| Measured power consumption off mode (Po)(W) | - |
| Sound power level (LWA)(dB) | 56 |

7704331110 185373382 AB en_US