

PRODUCT FICHE	
Energy Label Directive EU2010/30/EU-No65/2014 of range hoods	
Brand	ARÇELİK
Model	ADE 604 B
Annual Energy Consumption( AEC hood)(kWh/a)	59
Energy Efficiency Class	C
Fluid Dynamic Efficiency (FDE hood)	20,3
Fluid Dynamic Efficiency Class	C
Lighting Efficiency (LE hood) (lux/watt)	32
Lighting Efficiency Class	A
Grease Filtering Efficiency	66,0
Grease Filtering Efficiency Class	D
Air flow (m³/h) (min. and max. setting)	226-408
Air flow (m³/h) (boost setting)	-
Sound power level (dB) (min. and max. setting)	43-56
Sound power level (dB) (boost setting)	-
Measured power consumption in standby mode (Ps) (W)	0,25
Measured power consumption off mode (Po)(W)	-

7704331110 185373382 AB en\_US

**INSTRUCTION BOOKLET****Information for domestic range hoods**

Comply with EU directive 2009/125/EC Regulation No 66/2014

Brand	ARÇELİK
Model	ADE 604 B
Annual Energy Consumption( AEC hood)(kWh/a)	59
Time increase factor (f)	1,3
Fluid Dynamic Efficiency (FDE hood)	20,3
Energy Efficiency Index (EEI hood)	70,6
Measured air flow rate at best efficiency point (QBEP ) (m <sup>3</sup> /h)	271,1
Measured air pressure at best efficiency point (PBEP) (Pa)	319
Maximum air flow (Q max) (m <sup>3</sup> /h)	408
Measured electric power input at best efficiency point(WBEP) (W)	118
Nominal power of the lighting system (WL)(W)	5.5
Average illumination of the lighting system on the cooking surface (E middle)(lux)	175
Measured power consumption in standby mode (Ps) (W)	0,25
Measured power consumption off mode (Po)(W)	-
Sound power level (LWA)(dB)	56

7704331110 185373382 AB en\_US