| PRODUCT FICHE | |
|---|---|
| Energy Label Directive EU2010/30/EU-No65/2014 of range hoods | |
| Brand | Beko |
| Model | BDE 6062 G |
| Annual Energy Consumption( AEC hood)(kWh/a) | 58,5 |
| Energy Efficiency Class | A |
| Fluid Dynamic Efficiency (FDE hood) | 30 |
| Fluid Dynamic Efficiency Class | A |
| Lighting Efficiency (LE hood) (lux/watt) | 32 |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency | 76 |
| Grease Filtering Efficiency Class | C |
| Air flow ($m^3/h$) (min. and max. setting) | 220-445 |
| Air flow ($m^3/h$) (boost setting) | 720 |
| Sound power level (dB) (min. and max. setting) | 44-60 |
| Sound power level (dB) (boost setting) | 70 |
| Measured power consumption in standby mode (Ps) (W) | 0,25 |
| Measured power consumption off mode (Po)(W) | - |

7704331201 185373263 AB en_US

| INSTRUCTION BOOKLET | |
|---|---|
| **Information for domestic range hoods** | |
| Comply with EU directive 2009/125/EC Regulation No 66/2014 | |
| Brand | Beko |
| Model | BDE 6062 G |
| Annual Energy Consumption( AEC hood)(kWh/a) | 58,5 |
| Time increase factor (f) | 0,9 |
| Fluid Dynamic Efficiency (FDE hood) | 30 |
| Energy Efficiency Index (EEI hood) | 54 |
| Measured air flow rate at best efficiency point (QBEP ) ($m^3/h$) | 407,2 |
| Measured air pressure at best efficiency point (PBEP) (Pa) | 433,5 |
| Maximum air flow (Q max) ($m^3/h$) | 720 |
| Measured electric power input at best efficiency point(WBEP) (W) | 162,4 |
| Nominal power of the lighting system (WL)(W) | 5.5 |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) | 175 |
| Measured power consumption in standby mode (Ps) (W) | 0,25 |
| Measured power consumption off mode (Po)(W) | - |
| Sound power level (LWA)(dB) | 60 |

7704331201 185373263 AB en_US