| PRODUCT FICHE  |            |         |  |
|--|------------|---------|--|
| Energy Label Directive EU2010/30/EU-No65/2014 of range hoods |            |         |  |
| Brand  | ARÇELİK    |         |  |
| Model  | ADE 605 HB |         |  |
| Annual Energy Consumption( AEC hood)(kWh/a)                  |            | 56      |  |
| Energy Efficiency Class                                      |            | В       |  |
| Fluid Dynamic Efficiency (FDE hood)                          |            | 21,0    |  |
| Fluid Dynamic Efficiency Class                               |            | С       |  |
| Lighting Efficiency (LE hood) (lux/watt)                     |            | 30,0    |  |
| Lighting Efficiency Class                                    |            | Α       |  |
| Grease Filtering Efficiency                                  |            | 60,0    |  |
| Grease Filtering Efficiency Class                            |            | E       |  |
| Air flow (m³/h) (min. and max. setting)                      |            | 220-400 |  |
| Air flow (m³/h) (boost setting)                              |            | -       |  |
| Sound power level (dB) (min. and max. setting)               |            | 46-59   |  |
| Sound power level (dB) (boost setting)                       |            | -       |  |
| Measured power consumption in standby mode (Ps) (W)          |            | -       |  |
| Measured power consumption off mode (Po)(W)                  |            | -       |  |

7704331223 185373655 AB en\_US

| INSTRUCTION BOOKLET  |                         |       |
|--|-------------------------|-------|
| Information for domestic range hoods   |                         |       |
| Comply with EU directive 2009/125/E  | C Regulation No 66/2014 |       |
| Brand  | ARÇELİK                 |       |
| Model  | ADE 605 HB              |       |
| Annual Energy Consumption( AEC hood)(kWh/a)  |                         | 56    |
| Time increase factor (f)   |                         | 1,3   |
| Fluid Dynamic Efficiency (FDE hood)  |                         | 21,0  |
| Energy Efficiency Index (EEI hood)   |                         | 68,0  |
| Measured air flow rate at best efficiency point (QBEP) (m³/h)                      |                         | 240,0 |
| Measured air pressure at best efficiency point (PBEP) (Pa)                         |                         | 350,0 |
| Maximum air flow (Q max) (m³/h)  |                         | 400   |
| Measured electric power input at best efficiency point(WBEP) (W)                   |                         | 115,0 |
| Nominal power of the lighting system (WL)(W)                                       |                         | 7.0   |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) |                         | 175.0 |
| Measured power consumption in standby mode (Ps) (W)                                |                         | -     |
| Measured power consumption off mode (Po)(W)  |                         | -     |
| Sound power level (LWA)(dB)  |                         | 59    |

7704331223 185373655 AB en\_US