

**PRODUCT FICHE**

Energy Label Directive EU2010/30/EU-No65/2014 of range hoods

Brand	ARÇELİK
Model	ADE 906-2 S
Annual Energy Consumption( AEC hood)(kWh/a)	58,4
Energy Efficiency Class	A
Fluid Dynamic Efficiency (FDE hood)	30,8
Fluid Dynamic Efficiency Class	A
Lighting Efficiency (LE hood) (lux/watt)	104,0
Lighting Efficiency Class	A
Grease Filtering Efficiency	76,0
Grease Filtering Efficiency Class	C
Air flow (m³/h) (min. and max. setting)	280-435
Air flow (m³/h) (boost setting)	700
Sound power level (dB) (min. and max. setting)	51-61
Sound power level (dB) (boost setting)	71
Measured power consumption in standby mode (Ps) (W)	0,25
Measured power consumption off mode (Po)(W)	0,25

7705331101 185373279 AA en\_US

**INSTRUCTION BOOKLET****Information for domestic range hoods**

Comply with EU directive 2009/125/EC Regulation No 66/2014

Brand	ARÇELİK	
Model	ADE 906-2 S	
Annual Energy Consumption( AEC hood)(kWh/a)		58,4
Time increase factor (f)		0,9
Fluid Dynamic Efficiency (FDE hood)		30,8
Energy Efficiency Index (EEI hood)		53
Measured air flow rate at best efficiency point (QBEP ) (m <sup>3</sup> /h)		411,4
Measured air pressure at best efficiency point (PBEP) (Pa)		450
Maximum air flow (Q max) (m <sup>3</sup> /h)		700
Measured electric power input at best efficiency point(WBEP) (W)		166
Nominal power of the lighting system (WL)(W)		3.4
Average illumination of the lighting system on the cooking surface (E middle)(lux)		197
Measured power consumption in standby mode (Ps) (W)		0,25
Measured power consumption off mode (Po)(W)		0,25
Sound power level (LWA)(dB)		61

7705331101 185373279 AA en\_US