

PRODUCT FICHE

Energy Label Directive EU2010/30/EU-No65/2014 of range hoods

| | |
|---|-----------|
| Brand | ARÇELİK |
| Model | ADA 908 S |
| Annual Energy Consumption(AEC hood)(kWh/a) | 45,6 |
| Energy Efficiency Class | A+ |
| Fluid Dynamic Efficiency (FDE hood) | 36,4 |
| Fluid Dynamic Efficiency Class | A |
| Lighting Efficiency (LE hood) (lux/watt) | 30,0 |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency | 66,0 |
| Grease Filtering Efficiency Class | D |
| Air flow (m³/h) (min. and max. setting) | 190-400 |
| Air flow (m³/h) (boost setting) | 830 |
| Sound power level (dB) (min. and max. setting) | 44-60 |
| Sound power level (dB) (boost setting) | 74 |
| Measured power consumption in standby mode (Ps) (W) | 0,7 |
| Measured power consumption off mode (Po)(W) | - |

7706330103 185373836 AA en_US

INSTRUCTION BOOKLET**Information for domestic range hoods**

Comply with EU directive 2009/125/EC Regulation No 66/2014

| | |
|--|-----------|
| Brand | ARÇELİK |
| Model | ADA 908 S |
| Annual Energy Consumption(AEC hood)(kWh/a) | 45,6 |
| Time increase factor (f) | 0,7 |
| Fluid Dynamic Efficiency (FDE hood) | 36,4 |
| Energy Efficiency Index (EEI hood) | 44,2 |
| Measured air flow rate at best efficiency point (QBEP) (m ³ /h) | 345,0 |
| Measured air pressure at best efficiency point (PBEP) (Pa) | 570,0 |
| Maximum air flow (Q max) (m ³ /h) | 830 |
| Measured electric power input at best efficiency point(WBEP) (W) | 150,0 |
| Nominal power of the lighting system (WL)(W) | 10 |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) | 300,0 |
| Measured power consumption in standby mode (Ps) (W) | 0,7 |
| Measured power consumption off mode (Po)(W) | - |
| Sound power level (LWA)(dB) | 60 |

7706330103 185373836 AA en_US